

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
NEOLINEO-100										
NEOLINEO-100 T										
NEOLINEO-125										
NEOLINEO-125 T										
NEOLINEO-150										
NEOLINEO-150 T										
NEOLINEO-160										
NEOLINEO-160 T										
NEOLINEO-200/V-T										
NEOLINEO-200/V										
NEOLINEO-250/V	A	Estàtic	VSD no necessari	1.00	31.2	50.0	0.163	742	247	2465
NEOLINEO-315/V	A	Estàtic	VSD no necessari	1.00	35.3	51.2	0.307	996	392	2380