

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

η_e [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	η _e [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CBD/B-1919-4M 1/5/HE	A	Estàtic	VSD no necessari	1.00	33.4	44.0	0.208	1070	233	1394
CBD/B-1919-6M 1/10/HE	Exclòs ErP. Pe < 125 W									
CBD/B-2525-4M 1/2/HE	A	Estàtic	VSD no necessari	1.00	38.6	46.9	0.500	1969	353	1337
CBD/B-2525-4M 3/4/HE	A	Estàtic	VSD no necessari	1.00	39.2	47.3	0.528	2254	331	1356
CBD/B-2525-6M 1/5/HE	A	Estàtic	VSD no necessari	1.00	33.2	44.1	0.188	1815	123	907
CBD/B-2525-6M 1/3/HE	A	Estàtic	VSD no necessari	1.00	33.9	44.7	0.199	1686	144	964
CBD/B-2828-4M 1/2/HE	A	Estàtic	VSD no necessari	1.00	43.3	50.4	0.750	2490	469	1323
CBD/B-2828-4M 3/4/HE	A	Estàtic	VSD no necessari	1.00	43.2	50.4	0.739	2365	486	1317
CBD/B-2828-6M 1/3/HE	A	Estàtic	VSD no necessari	1.00	37.6	46.7	0.368	2336	213	947
CBD/B-3333-6T 1 1/2/HE	A	Estàtic	VSD no necessari	1.00	38.7	44.8	1.119	4588	340	853
CBD/B-3333-6M 3/4/HE	A	Estàtic	VSD no necessari	1.00	40.4	47.7	0.699	3057	332	932
CBD/B-3333-6M 1/HE	A	Estàtic	VSD no necessari	1.00	38.3	44.8	0.948	4198	311	852
CBD/B-3939-6T 3/HE	A	Estàtic	VSD no necessari	1.00	44.6	49.3	1.803	6400	453	942