

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category	[m³/h]	Flow rate	ηe [%]	Efficiency
EC	Efficiency category	[Pa]	Static pressure or total (depending on EC)	N	Efficiency grade
VSD	Variable Speed Drive	[RPM]	Rotation per minute	[kW]	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
NEOLINEO/EW-100			Exclòs ErP. Pe < 125 W							
NEOLINEO/EW-125			Exclòs ErP. Pe < 125 W							
NEOLINEO/EW-150			Exclòs ErP. Pe < 125 W							
NEOLINEO/EW-160			Exclòs ErP. Pe < 125 W							
NEOLINEO/EW-200	A	Estàtic	VSD incorporat al ventilador	1.00	46.3	57.5	0.168	780	360	2950
NEOLINEO/EW-250	A	Estàtic	VSD incorporat al ventilador	1.00	48.3	58.4	0.249	981	441	2950