

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CAST-400-2T-3 IE3										Exclude. Transport materials
CAST-450-2T-4 IE3										Exclude. Transport materials
CAST-450-2T-5.5 IE3										Exclude. Transport materials
CAST-500-2T-7.5 IE3										Exclude. Transport materials
CAST-500-2T-10 IE3										Exclude. Transport materials
CAST-560-2T-15 IE3										Exclude. Transport materials
CAST-630-2T-20 IE3										Exclude. Transport materials
CAST-630-2T-25 IE3										Exclude. Transport materials
CAST-710-2T-30 IE3										Exclude. Transport materials
CAST-710-2T-40 IE3										Exclude. Transport materials
CAST-710-2T-50 IE3										Exclude. Transport materials
CAST-800-4T-10 IE3										Exclude. Transport materials
CAST-900-4T-15 IE3										Exclude. Transport materials
CAST-900-4T-20 IE3										Exclude. Transport materials
CAST-1000-4T-25 IE3										Exclude. Transport materials