

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ErP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flowrate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
NEOLINEO/EW-100										
ErP Exclude. Pe < 125 W										
NEOLINEO/EW-125										
ErP Exclude. Pe < 125 W										
NEOLINEO/EW-150										
ErP Exclude. Pe < 125 W										
NEOLINEO/EW-160										
ErP Exclude. Pe < 125 W										
NEOLINEO/EW-200	A	Static	VSD built-in to the fan	1.00	46.3	57.5	0.168	780	360	2950
NEOLINEO/EW-250	A	Static	VSD built-in to the fan	1.00	48.3	58.4	0.249	981	441	2950