

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP).

<b>MC</b>	Measurement category	<b>[m<sup>3</sup>/h]</b>	Flowrate	<b>η<sub>e</sub> [%]</b>	Efficiency
<b>EC</b>	Efficiency category	<b>[Pa]</b>	Static pressure or total (depending on EC)	<b>N</b>	Efficiency grade
<b>VSD</b>	Variable Speed Drive	<b>[RPM]</b>	Rotation per minute	<b>[kW]</b>	Input power
<b>SR</b>	Specific ratio				

Model	MC	EC	VSD	SR	η <sub>e</sub> [%]	N	[kW]	[m <sup>3</sup> /h]	[Pa]	[RPM]
CMP/EC-616-2M-0.75 IE5	A	Static	VSD built-in to the fan	1.00	44.2	60.4	0.286	639	712	2910
CMP/EC-620-2M-0.5 IE5	A	Static	VSD built-in to the fan	1.00	47.3	61.7	0.422	699	1026	2910
CMP/EC-718-2M-1 IE5	A	Static	VSD built-in to the fan	1.00	42.4	55.7	0.543	909	913	2910
CMP/EC-820-2M-1.5 IE5	A	Static	VSD built-in to the fan	1.00	53.1	65.9	0.597	935	1219	2910
CMP/EC-922-4M-0.75 IE5	A	Static	VSD built-in to the fan	1.00	46.3	63.3	0.242	1187	339	1410
CMP/EC-1025-4M-1.5 IE5	A	Static	VSD built-in to the fan	1.00	45.2	59.4	0.440	1519	470	1410